Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- 1-11. (Cancelled)
- 12. (Currently Amended) A fusible conductor for a fuse element, said fusible conductor comprising:

an electrically insulating core;

a fusible wire wound about <u>and in contact with</u> the core forming a plurality of <u>first</u> windings; and

an electrically insulated fibre wound about the core <u>forming a plurality of second</u> windings and disposed between each of said plurality of fusible wire windings such that wherein the insulating fibre of <u>each of the second windings</u> is adjacent <u>a surface of the</u> fusible wire of a subsequent <u>one of the second windings winding</u>.

- 13. (Cancelled)
- 14. (Previously Presented) The fusible conductor of claim 12, wherein both fusible wires and also the insulting fibre have an approximately circular cross section and the ratio of the diameter of the fusible wire to that of the insulating fibre is between 1/3 and 3.
- 15. (Previously Presented) The fusible conductor of claim 14, wherein the ratio of the diameter of the fusible wire to that of the insulating fibre is between 1 and 3.
- 16. (Previously Presented) The fusible conductor of claim 12, wherein the fusible wire has an approximately circular cross section and wherein the insulating fibre is

Docket No.: 1511FS0189

TC/A.U. 2835

situated between adjacent turns of the fusible wire such that the spacing between the turns is 0.2 to 2 time the diameter of the fusible wire.

- 17. (Previously Presented) The fusible conductor of claim 16, wherein the spacing between turns is smaller than the diameter of the fusible wire
- 18. (Previously Presented) The fusible conductor of claim 16, wherein the outer surface of the wound fusible wire projects beyond the outer surface of the insulating fibre.
- 19. (Previously Presented) The fusible conductor of claim 14, wherein the core has a circular cross section and the cross sectional dimensions of the insulating fibre are smaller than the diameter of the core.
- 20. (Currently Amended) The fusible conductor of claim [[1]] <u>12</u>, wherein the insulating fibre consists of one or more glass fibres.
- 21. (Currently Amended) The fusible conductor of claim [[1]] 12, wherein the insulating fibre consists of one or more ceramic fibres.
- 22. (Currently Amended) The fusible conductor of claim [[1]] <u>12</u>, wherein the core consists of one or more glass fibres.
- 23. (Withdrawn) The fusible conductor of claim 12 wherein said insulating fibre has an approximately circular cross section having a given diameter and is configured to deform to a flattened strip when wound about said core.
- (Withdrawn) A fusible conductor for a fuse element comprising:an electrically insulating core;a fusible wire wound about said core forming a plurality of windings;

Appl. No. 10/596,829 Response Dated February 9, 2011 Reply to Office Action of August 9, 2010

said core.

an insulating fibre wound about the core and disposed between each of said plurality of fusible wire windings such that the insulating fibre is adjacent a fusible wire of a subsequent winding, said insulating fiber having an approximately circular cross section and configured to deform to a relatively flat cross section when wound around

Docket No.: 1511FS0189

TC/A.U. 2835

Examiner: Vortman, Anatoly